

# alicon *Super* SERIES

**POWERFUL &  
PRODUCTIVE**

Now with

**12  
Months**

Warranty\*

\* Conditions Apply



## IMPROVED DURABILITY

- **Longer Piston & Damper** ensures better Anti-Blank Firing protection. ABF function helps to protect internal components.
- **Larger Through Bolt** protects against bolt breakage and extends component life.
- **Modified Front Cover:** Enhanced durability due to the larger diameter and integrated greasing port.

## HIGHER PERFORMANCE

- **Enhanced Productivity** due to higher impact energy.
- **Larger Head Cap** containing more N<sub>2</sub> gas which helps to create higher impact energy.
- **Larger Chisel & Front Head** Improves front head life and the product performance.



Description	Unit	B145 Super+
Suitable Excavator	ton	10-15
Max. Hydraulic Input Power	kW	32.5
Control Valve Type	-	External Type
Operating Weight	kg	959
Overall Length	mm	2,263
Chisel Out Diameter	mm	105
Chisel Length	mm	975
Setting Pressure	bar	190
Working Pressure	bar	120-160
Oil Flow	L/min	90-110
Blow Rate (Long Stroke)	BPM	350-550
Back Head N <sub>2</sub> Gas Pressure	kgf/cm <sup>2</sup>	13
Adjustable BPM Valve	-	Available



Description	Unit	B215 Super+
Suitable Excavator	ton	18-25
Max. Hydraulic Input Power	kW	40
Control Valve Type	-	External Type
Operating Weight	kg	1,817
Overall Length	mm	2,841
Chisel Out Diameter	mm	135
Chisel Length	mm	1,300
Setting Pressure	bar	210
Working Pressure	bar	130-170
Oil Flow	L/min	110-160
Blow Rate (Long Stroke)	BPM	350-500
Back Head N <sub>2</sub> Gas Pressure	kgf/cm <sup>2</sup>	12
Adjustable BPM Valve	-	Available

## Shape of Chisel

Classification	Major Contents	
Moil		Concrete, Rocks, Pavements, Slopes
Wedge		Trench, Slopes, Finishing
Blunt		Quarries
Conical		Concrete, Rocks, Pavements



Description	Unit	B235 Super+
Suitable Excavator	ton	18-25
Max. Hydraulic Input Power	kW	50
Control Valve Type	-	External Type
Operating Weight	kg	1,856
Overall Length	mm	2,841
Chisel Out Diameter	mm	140
Chisel Length	mm	1,300
Setting Pressure	bar	210
Working Pressure	bar	130-180
Oil Flow	L/min	130-170
Blow Rate (Long Stroke)	BPM	250-400
Back Head N <sub>2</sub> Gas Pressure	kgf/cm <sup>2</sup>	13
Adjustable BPM Valve	-	Available

**Tata Hitachi Construction Machinery Company Private Limited**  
 Registered Office: Jubilee Building, 45, Museum Road, Bengaluru – 560 025  
 Telephone: +91 80 6695 3301 / 02 / 03 / 04 / 05 | Toll Free: 1800 121 6633  
 Email: [info@tatahitachi.co.in](mailto:info@tatahitachi.co.in) | Website: [www.tatahitachi.co.in](http://www.tatahitachi.co.in)

Tata Hitachi Authorised Dealer: